#### HEATY COMPLETE PROFESSIONAL SERIES

Fully automatic filling and refilling station with cloud and IoT connection - The smart revolution of water replenishment



## Technical data

Art.-No. 100392 Art.-No. 100392-OFK

## **Heaty Complete PROfessional + OFK**

3/4" AG for ÜWM flat sealing Connection thread Max. operating temperature 40 °C Max. filling capacity\* 65 l/h 6 bar Max. operating pressure Capacity at 420 µS/cm\*\* 122,5 l Pressure reducer adjustable Electrical connection 230 V/50 Hz Built-in length 340 mm Flat sealing to flat sealing with filling combination and shut-off valve

The Heaty Complete PROfessional OFKseries

does not have a system separator.

Cloud protects against claims for recourse by recording every work step and every replenishment. Proactive communication minimizes unnecessary service calls through targeted trips. The connection to the cloud enables a comprehensive overview of all refills and customers. Status updates on cartridge changes, software updates and device history are available at any time. Early error detection and easy correction are guaranteed. Welcome to the future of fully automatic water refills.

The user-friendly menu navigation reduces the

potential for errors to a minimum, while the

integrated leak protection warns of water da-

mage. The documentation in the UWS Master


# Including

- Refill cartridge with 0.8 | Vadion pH-Control
- Filling combination BA 1/2"
- Digital water meter
- Digital capacitance measurement
- Keyless venting
- Key for cartridge and union nut
- Mounting material
- Connection fittings ¾" ÜWM x ½" AG
- System separator BA
- Shut-off valves
- Integrated flow limiter
- Screen seal against resin ingress
- Optional: Water supply from above
- Integrated data interface via mobile network
- Leak protection

#### Your benefits

- Automatic connection via the mobile data network, no setup required
- ✓ Continuous monitoring with proactive alerts
- 5-year Complete PROfessional package including 2 refill cartridges and cloud connection
- Safety: Documentation of the amount of treated and untreated water via integrated water meter
- ✓ Plannable service calls thanks to proactive communication
- Controlled refilling for sustainable heating water quality
- ✓ Leakage protection with push notification
- Alarm message when capacity falls below
- ✓ Digital capacity displays (resin and battery)
- ✓ Short installation length of only 34 cm
- \* Dependent on system and network pressure.
- \*\* The capacity specifications are based on the ideal case (12°dH / 21°fH). Deviations may occur due to application errors, water quality and temperature.







#### HEATY COMPLETE PROFESSIONAL SERIES

Fully automatic filling and refilling station with cloud and IoT connection - The smart revolution of water replenishment



## Technical data

Art.-No. 100393 Art.-No. 100393-OFK

# **Heaty Complete PROfessional XL + OFK**

Connection thread 3/4" AG for ÜWM flat sealing Max. operating temperature 40 °C Max. filling capacity\* 120 l/h 6 bar Max. operating pressure Capacity at 420 µS/cm\*\* 225 I Pressure reducer adjustable Electrical connection 230 V/50 Hz Built-in length 340 mm Flat sealing to flat sealing with filling combination and shut-off valve

The Heaty Complete PROfessional OFKseries

does not have a system separator.

trips. The connection to the cloud enables a comprehensive overview of all refills and customers. Status updates on cartridge changes, software updates and device history are available at any time. Early error detection and easy correction are guaranteed.

Welcome to the future of fully automatic water

The user-friendly menu navigation reduces

the potential for errors to a minimum, while

the integrated leak protection warns of water

damage. The documentation in the UWS Mas-

ter Cloud protects against claims for recourse by recording every work step and every rep-

lenishment. Proactive communication minimi-

zes unnecessary service calls through targeted

refills.

# Including

- Refill cartridge with 1.5 | Vadion pH-Control
- Filling combination BA 1/2"
- Digital water meter
- Digital capacitance measurement
- Keyless venting
- Key for cartridge and union nut
- Mounting material
- Connection fittings ¾" ÜWM x ½" AG
- System separator BA
- Shut-off valves
- Integrated flow limiter
- Screen seal against resin ingress
- Optional: Water supply from above
- Integrated data interface via mobile network
- Leak protection

#### Your benefits

- Automatic connection via the mobile data network, no setup required
- ✓ Continuous monitoring with proactive alerts
- 5-year Complete PROfessional package including 2 refill cartridges and cloud connection
- Safety: Documentation of the amount of treated and untreated water via integrated water meter
- ✓ Plannable service calls thanks to proactive communication
- ✓ Controlled refilling for sustainable heating water quality
- ✓ Leakage protection with push notification
- √ Alarm message when capacity falls below
- ✓ Digital capacity displays (resin and battery)
- ✓ Short installation length of only 34 cm
- Dependent on system and network pressure.
- \*\* The capacity specifications are based on the ideal case (12°dH / 21°fH). Deviations may occur due to application errors, water quality and temperature.



