

HEATY FILTRA ADVANCED № 2

For cleaning the systems from dirt, sludge and deposits



Including

- Stainless steel filter housing
- Filter capacity indicator
- Shut-off devices
- Discharge tap
- 3x filter bags 1µm
- Quick-release fasteners at inlet and outlet
- Hose set
- Dual filter (magnetite and fine filter)
- Hot water pump
- Adjustable volume flow meter

These components are fully assembled on a large hand truck with rubber tyres and skids.

Technical data

Item no. 100453-FL
Item no. Replacement filter 100451

Max. Filtration capacity at <math><1\mu\text{m}</math>	3,600 l/h
Max. Flow pressure	6 bar
Max. Operating temperature	80 °C
Magnetic field strength (Gauss)	11 x 12,000
Height / width / depth (approx.)	1,170 / 480 / 470 mm
Weight (approx.)	34 kg
Power connection required	230 V

Heaty Filtra Advanced № 2

Why a filtration device?

Water that is free of dirt, suspended matter, solid material or other deposits:

- prevents clogging of pumps or heat exchangers,
- promotes good heat transfer,
- reduces material wear and
- reduces the risk of germ formation

Your advantages

- ✓ High filtration performance
- ✓ 1µm fine filtration
- ✓ Simple operation
- ✓ Suitable for hot water
- ✓ Discharge tap for checking during operation
- ✓ Quick filter change
- ✓ Connection for pressure gauge



Please note:

The medium used must not be volatile (hot water up to 95 °C).

