

# HEATY MINI PH LED

For heating water treatment in hot-water area (up to 50 °C)



## Including

- Synthetic container (filled with 6 litre mixed bed Vadion pH-Control)
- Water meter, shut-off fittings
- Removal tap for control
- Funnel for easy refilling
- Integrated flow limiter
- Carrier handle
- Non-return valve
- Sieve seal against resin ingress
- LED measuring cell

## Technical data Order number 100105

Max. filling performance*	360 l/h
Min. flow pressure	1,5 bar
Max. operating pressure	8 bar
Max. operating temperature	50 °C
Height / Width / Depth (appr.)	710 / 320 / 170 mm
Weight (appr.)	9,2 kg
Mixed bed contents	6 l
Capacity for 420 µS/cm to < 100**	900 l
Electricity connection required	Yes, for LED

## Heaty Mini pH LED

Ideal for very small amounts during repairs and difficult to reach systems to be filled, e.g. blocks of flats with single-storey heating.



Suitable for hot water up to 50 °C



Max. filling performance 360 l/h\*

## Your advantages

- ✓ Including
- ✓ Ideal for customer service and small filling quantities
- ✓ Comply with VDI 2035, ÖNORM H 5195-1 and SWKI BT 102-1 standards in one step
- ✓ Easy handling
- ✓ Safety due to LED measurement
- ✓ By filling with Vadion pH-Control only one working step is necessary

\* Depends on system and network pressure.

\*\* The capacity data are based on the ideal case. Misapplication, water quality and temperature may lead to deviations.

