

HEATY SMART HW SERIES

Complete unit for professional bypass treatment and magnetite filtration in the hot water range (up to 80 °C)



Including

- Synthetic container (filled with 9.5 litres mixed bed Vadion pH-Control)
- Water meter and shut-off devices
- Removal tap for better control
- Funnel for easy refilling
- Run-over protection, carrying handle
- Solid rubber wheels
- Check valve
- Integrated sieve seal against resin ingress
- LED measuring cell

These components are completely mounted on the Heaty Smart S, including bag cart, MagnaClean®Professional2XP, circulation pump and hose set.

Technical data

Art.-No. 100410

Max. filling performance*	600 l/h
Min. flow pressure	1.5 bar
Max. operating pressure	6 bar
Max. operating temperature	80 °C
Height / width / depth (approx.)	1.200 / 500 / 560 mm
Weight (approx.)	38.9 kg
Mixed bed contents	9.5 l
Capacity for 420 µS/cm to < 100**	1,350 l
Electricity connection required	Yes, for LED and pump

Heaty 50 Smart HW



Suitable for hot water up to 80 °C



Can be used with bypass up to 80 °C water temperature



Max. filling performance 600 l/h*

* Depending on system pressure and mains pressure.

** The capacity figures are based on the ideal case. There may be variations due to errors in usage, water quality and temperature.

Your advantages

- ✓ Pre-installed unit for professional bypass treatment
- ✓ Safety, simple and flexible bypass condition
- ✓ Magnetite filtration through built-in magnetic filter
- ✓ System independent due to integrated hot water pump
- ✓ Compatible with condition cartridges of all sizes



HEATY SMART HW SERIES

Complete unit for professional bypass treatment and magnetite filtration in the hot water range (up to 80 °C)



Including

- Synthetic container (filled with 23 litres mixed bed Vadion pH-Control)
- Water meter and shut-off devices
- Removal tap for better control
- Funnel for easy refilling
- Run-over protection, carrying handle
- Solid rubber wheels
- Check valve
- Integrated sieve seal against resin ingress
- LED measuring cell

These components are completely mounted on the Heaty Smart M, including bag cart, MagnaClean®Professional2XP, circulation pump and hose set.

Technical data

Art.-No. 100411

Heaty 100 Smart HW PLUS

Max. filling performance*	1,200 l/h
Min. flow pressure	1.5 bar
Max. operating pressure	6 bar
Max. operating temperature	80 °C
Height / width / depth (approx.)	1.200 / 500 / 560 mm
Weight (approx.)	47.2 kg
Mixed bed contents	23 l
Capacity for 420 µS/cm to < 100**	3,420 l
Electricity connection required	Yes, for LED and pump



Suitable for hot water up to 80 °C



Can be used with bypass up to 80 °C water temperature



Max. filling performance 1,200 l/h*

* Depending on system pressure and mains pressure.

** The capacity figures are based on the ideal case. There may be variations due to errors in usage, water quality and temperature.

Your advantages

- ✓ For professional bypass condition in combination with the filling devices of our „Heaty 100 small-serie“
- ✓ Safety, simple and flexible bypass condition
- ✓ Magnetite filtration through built-in magnetic filter
- ✓ System independent due to integrated hot water pump
- ✓ Compatible with condition cartridges of all sizes

